

MODEL#: DVR7704HT

4 Channel H.264 Hexaplex Realtime Network DVR, VGA Output, Support Mobile Phone Surveillance



SPECIFICATIONS

4 Channel H.264 Hexaplex Realtime Network DVR

- 4-Ch H.264 DVR, Real-time CIF Recording, Real-time Display up to 704 x 480 (D1)
- Hexaplex Operation: Simultaneously Record, Live, Playback, Control, Back-up, Remote Access and Mobile Phone Live View
- Support Remote View via 3G Mobile Phone (Windows Mobile, Symbian and iPhone)
- Two USB interface: USB 2.0 for data backup; USB1.1 for Mouse operation, USB Mouse Included
- IE Based Network Monitor, Playback & Backup
- DDNS & Email Support
- Programmable Schedule, Motion Detection & Sensor Triggered Recording
- Support 1 SATA HDD up to 1TB
- Video Backup: USB Flash Disk / Removable USB HDD, USB Burnner / Network Backup to AVI File format
- BNC Video 4 In / 2 Out, 1 x VGA Output, Audio Support 4/1, Alarm Support 4/1
- PTZ Control: Built-in RS-485 port, supports PELCO-P & PELCO-D

Video System	NTSC
Video Compression Format	H.264
Video Input Channel	4 BNC
Video Output Channel	2 BNC Video Output, 1 VGA Output
Video Display Modes	Full Screen, Quad Channels
Video Display Frame Rate	NTSC: 120FPS
Resolution Display	NTSC: Up to 720 x 480
Resolution Recording	NTSC: 352 x 240 (CIF), 352 x 480 (HD1), 704 x 480 (D1)
Resolution Modes	Continuous, Motion Detection, Sensor Triggered, Time Schedule
Recording Compression	H.264
Recording Frame Rate	NTSC: 120FPS (CIF)
Audio I/O	4-CH RCA Audio Input / 1-CH RCA Audio Output
Video Recording Mode	Always / Schedule / Manual / Motion Detection / Sensor Triggered

Recording Quality	Low, Standard, High, Highest
Playback Search Mode	Date/ Time, Event, Archived Files
Storage	1 SATA HDD. Max. up to 1TB
Backup Device	USB Flash Disk / Removable USB HDD, USB Burnner / Network Backup AVI File
Alarm I/O	4-CH Alarm Input, 1-CH Alarm Output
Alarm Type	Motion / Sensor Triggered / Video Loss / HDD Space / HDD Loss
USB Port	USB1.1 for Mouse Operation USB 2.0 for Removable HDD/Burnner, or USB Flash Drive
Network Connection	10/100 Ethernet (RJ-45)
Network Protocol	TCP/IP, Static IP, DHCP, PPPOE, DDNS, UDP
Network Function	Support remotely live view via mobile phone and real time monitoring via IE browser and/or network; support remote management.
Network Remote Users	Up to 20 Users Simultaneously
PTZ	Built-in RS-485 port, supports PELCO-P & PELCO-D
Power Adapter	Input: AC100~240V 47~63Hz, Output: DC19V, 1A
Power Consumption	Max. 18W
USB Mouse	Included
Dimension	15" x 13.60" x 3.76"
Weight	6 lbs